

Clean Up Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date: 04/15/2015

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Identification

Product form : Mixture
Product name : Clean Up
Product code : 1192-7807

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Degreaser.

1.3. Details of the supplier of the safety data sheet

J. Racenstein Co. 20925 Chico Street Carson, CA 90745 T (800) 221-3748

1.4. Emergency telephone number

Emergency number : (800) 535-5053

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

Classification (GHS-US)

Skin Irrit. 2 H315 - Causes skin irritation Full text of H-phrases: see section 16

2.2. Label elements

GHS-US labeling

Hazard pictograms (GHS-US)



GHS07

Signal word (GHS-US) : Warning

Hazard statements (GHS-US) : H315 - Causes skin irritation

Precautionary statements (GHS-US) : P264 - Wash hands and forearms thoroughly after handling

P280 - Wear protective gloves/eye protection/face protection P302+P352 - If on skin: Wash with plenty of soap and water P321 - Specific treatment (see First aid measures on this label) P332+P313 - If skin irritation occurs: Get medical advice/attention P362+P364 - Take off contaminated clothing and wash it before reuse

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

07/16/2015 EN (English US) Page 1

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Name	Product identifier	%	Classification (GHS-US)
butyl glycolether	(CAS No) 111-76-2	5 - 10	Flam. Liq. 4, H227 Acute Tox. 3 (Dermal), H311 Acute Tox. 2 (Inhalation:gas), H330 Skin Irrit. 2, H315 Eye Irrit. 2A, H319
dodecylbenzenesulphonic acid	(CAS No) 27176-87-0	1 - 5	Acute Tox. 4 (Oral), H302 Skin Corr. 1A, H314
Disodium metasilicate	(CAS No) 6834-92-0	1 - 5	Skin Corr. 1B, H314 STOT SE 3, H335
Potassium Hydroxide, 45%= <conc<50%, aqueous="" solutions<="" td=""><td>(CAS No) 1310-58-3</td><td>1 - 5</td><td>Acute Tox. 3 (Oral), H301 Skin Corr. 1A, H314</td></conc<50%,>	(CAS No) 1310-58-3	1 - 5	Acute Tox. 3 (Oral), H301 Skin Corr. 1A, H314

Full text of H-phrases: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general

: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical

advice (show the label where possible).

First-aid measures after inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing. Immediately

call a poison center or doctor/physician.

First-aid measures after skin contact : Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

Immediately call a poison center or doctor/physician.

First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to

do. Continue rinsing. Immediately call a poison center or doctor/physician.

First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Immediately call a poison center or doctor/physician.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries : Causes severe skin burns and eye damage.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Water spray. Sand.

Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Reactivity : Thermal decomposition generates : corrosive vapors.

5.3. Advice for firefighters

Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any

chemical fire. Prevent fire-fighting water from entering environment.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection.

Emergency procedures : Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect

spillage. Store away from other materials.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

07/16/2015 EN (English US) 2/8

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation

of vapor. Do not breathe dust/mist/spray. Avoid contact during pregnancy/while nursing.

Hygiene measures : Wash hands and forearms thoroughly after handling.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Comply with applicable regulations.

Storage conditions : Keep only in the original container in a cool, well ventilated place away from heat, hot surfaces,

sparks, open flame and other ignition sources. No smoking. Keep container closed when not in

use.

Incompatible products : Strong bases. Strong acids.
Incompatible materials : Sources of ignition. Direct sunlight.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Potassium Hydroxide, 45%= <conc<50%, (1310-58-3)<="" aqueous="" solutions="" th=""></conc<50%,>			
ACGIH	Remark (ACGIH)	URT, eye, & skin irr	
butyl glycolether (111-76-2)			
ACGIH	ACGIH TWA (ppm)	20 ppm (2-Butoxyethanol (EGBE); USA; Time- weighted average exposure limit 8 h; TLV - Adopted Value)	
ACGIH	Remark (ACGIH)	Eye & URT irr	
OSHA	OSHA PEL (TWA) (mg/m³)	240 mg/m³	
OSHA	OSHA PEL (TWA) (ppm)	50 ppm	

8.2. Exposure controls

Personal protective equipment : Avoid all unnecessary exposure.

Hand protection : Wear protective gloves/eye protection/face protection protective gloves.

Eye protection : Chemical goggles or face shield. Skin and body protection : Wear suitable protective clothing.

Respiratory protection : Wear appropriate mask.

Other information : Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid
Color : Green
Odor : mild

Odor threshold : No data available

pH : 13

 Melting point
 : No data available

 Freezing point
 : No data available

 Boiling point
 : $212 - 220 \, ^{\circ}$ F

 Flash point
 : ≥ $200 \, ^{\circ}$ F

Relative evaporation rate (butyl acetate=1) : No data available Flammability (solid, gas) : No data available Explosion limits : No data available Explosive properties : No data available Oxidizing properties : No data available Vapor pressure : No data available

07/16/2015 EN (English US) 3/8

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Relative density : 1.03

Relative vapor density at 20 °C : Same as water Solubility Soluble in water.

Water: Solubility in water of component(s) of the mixture :

•: > 18 g/100ml •: •: •: 103 g/100ml •: 42 g/100ml •: 66 g/100ml

Log Pow : No data available : No data available Auto-ignition temperature Decomposition temperature : No data available Viscosity : No data available

Viscosity, kinematic : No data available Viscosity, dynamic : No data available

Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Thermal decomposition generates: corrosive vapors.

Chemical stability

Stable under normal conditions. Not established.

Possibility of hazardous reactions

Not established.

Conditions to avoid 10.4.

Direct sunlight. Extremely high or low temperatures.

Incompatible materials

Strong acids. Strong bases.

10.6. **Hazardous decomposition products**

Fume. Carbon monoxide. Carbon dioxide. Thermal decomposition generates : corrosive vapors.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

: Not classified Acute toxicity

Disodium metasilicate (6834-92-0)		
LD50 dermal rat	> 5000 mg/kg body weight (Rat; Read-across; OECD 402: Acute Dermal Toxicity)	
dodecylbenzenesulphonic acid (27176-87-0)	, , , , , , , , , , , , , , , , , , , ,	
LD50 oral rat	650 mg/kg (Rat; Literature study)	
ATE US (oral)	650.000 mg/kg body weight	
Potassium Hydroxide, 45%= <conc<50%, (1310-58-3)<="" agueous="" solutions="" td=""></conc<50%,>		
LD50 oral rat	273 mg/kg (Rat)	
ATE US (oral)	273.000 mg/kg body weight	
butyl glycolether (111-76-2)		
LD50 dermal rat	> 2000 mg/kg body weight (Rat; Experimental value; OECD 402: Acute Dermal Toxicity)	
LD50 dermal rabbit	435 mg/kg body weight (Rabbit; Experimental value; OECD 402: Acute Dermal Toxicity; 435 mg/kg bodyweight; Rabbit; Weight of evidence; Equivalent or similar to OECD 402)	
LC50 inhalation rat (mg/l)	2.17 mg/l/4h (Rat; Experimental value; 2.35 mg/l/4h; Rat; Experimental value)	
LC50 inhalation rat (ppm)	450 - 486 ppm/4h 450-486,Rat	
ATE US (dermal)	435.000 mg/kg body weight	
ATE US (gases)	450.000 ppmV/4h	
ATE US (vapors)	2.170 mg/l/4h	
ATE US (dust, mist)	2.170 mg/l/4h	
Skin corrosion/irritation	: Causes skin irritation.	
	pH: 13	

07/16/2015 EN (English US) 4/8

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Serious eye damage/irritation : Not classified pH: 13

Respiratory or skin sensitization : Not classified Germ cell mutagenicity : Not classified Carcinogenicity : Not classified

butyl glycolether (111-76-2)

 IARC group
 3 - Not classifiable

 Reproductive toxicity
 : Not classified

 Specific target organ toxicity (single exposure)
 : Not classified

Specific target organ toxicity (repeated

exposure)

: Not classified

Aspiration hazard : Not classified

Potential Adverse human health effects and

symptoms

: Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1. Toxicity

Disodium metasilicate (6834-92-0)		
LC50 fish 1	210 mg/l (LC50; Equivalent or similar to OECD 203; 96 h; Brachydanio rerio; Semi-static system; Fresh water; Experimental value)	
Threshold limit algae 1	207 mg/l (EC50; DIN 38412-9; 72 h; Scenedesmus subspicatus; Fresh water)	
dodecylbenzenesulphonic acid (27176-87-0)		
LC50 fish 1	4.2 mg/l (96 h; Salmo gairdneri (Oncorhynchus mykiss); Fresh water)	
EC50 Daphnia 1	5.5 mg/l (48 h; Daphnia magna)	
LC50 fish 2	6 mg/l (96 h; Brachydanio rerio; Fresh water)	
Threshold limit algae 2	127.9 mg/l (ErC50; Other; 72 h; Scenedesmus subspicatus; Static system)	
Potassium Hydroxide, 45%= <conc<50%, (1310-58-3)<="" aqueous="" solutions="" td=""></conc<50%,>		
LC50 fish 2	80 mg/l (LC50: 96 h)	

12.2. Persistence and degradability

Clean Up		
Persistence and degradability	Not established.	
Disodium metasilicate (6834-92-0)		
Persistence and degradability	Biodegradability: not applicable. No (test)data on mobility of the substance available. Not established.	
Biochemical oxygen demand (BOD)	Not applicable	
Chemical oxygen demand (COD)	Not applicable	
ThOD	Not applicable	
dodecylbenzenesulphonic acid (27176-87-0)		
Persistence and degradability	Readily biodegradable in water. Low potential for adsorption in soil.	
Chemical oxygen demand (COD)	2.41 g O ₂ /g substance	
Potassium Hydroxide, 45%= <conc<50%, aqu<="" td=""><td>eous solutions (1310-58-3)</td></conc<50%,>	eous solutions (1310-58-3)	
Persistence and degradability	Biodegradability: not applicable. No (test)data on mobility of the components available.	
Biochemical oxygen demand (BOD)	Not applicable	
Chemical oxygen demand (COD)	Not applicable	
ThOD	Not applicable	
butyl glycolether (111-76-2)		
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. Photodegradation in the air.	

07/16/2015 EN (English US) 5/8

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

butyl glycolether (111-76-2)	
Biochemical oxygen demand (BOD)	0.71 g O₂/g substance
Chemical oxygen demand (COD)	2.20 g O₂/g substance
ThOD	2.305 g O₂/g substance
BOD (% of ThOD)	0.31

12.3. Bioaccumulative potential

Clean Up			
Bioaccumulative potential	Not established.		
Disodium metasilicate (6834-92-0)	Disodium metasilicate (6834-92-0)		
Bioaccumulative potential	Bioaccumulation: not applicable. Not established.		
dodecylbenzenesulphonic acid (27176-87-0)			
Log Pow	1.96		
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).		
Potassium Hydroxide, 45%= <conc<50%, (1310-58-3)<="" aqueous="" solutions="" td=""></conc<50%,>			
Bioaccumulative potential	Not bioaccumulative.		
butyl glycolether (111-76-2)			
Log Pow	0.81 (Experimental value; BASF test; 25 °C)		
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).		

12.4. Mobility in soil

dodecylbenzenesulphonic acid (27176-87-0)	
Surface tension	35 N/m (25 °C; 800 mg/l)
butyl glycolether (111-76-2)	
Surface tension	0.027 N/m (25 °C)

12.5. Other adverse effects

Effect on the global warming : No known ecological damage caused by this product.

Other information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Dispose of

contents/container in accordance with local/regional/national/international regulations.

Ecology - waste materials : Avoid release to the environment.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT Not regulated for transport

TDG

No additional information available

Transport by sea

No additional information available

Air transport

No additional information available

SECTION 15: Regulatory information

15.1. US Federal regulations

Disodium metasilicate (6834-92-0)

Not listed on the United States TSCA (Toxic Substances Control Act) inventory

07/16/2015 EN (English US) 6/8

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

dodecylbenzenesulphonic acid (27176-87-0)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory Not listed on the United States SARA Section 313	
RQ (Reportable quantity, section 304 of EPA's List of Lists)	1000 lb

Potassium Hydroxide, 45%=<conc<50%, aqueous solutions (1310-58-3)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Not listed on the United States SARA Section 313

RQ (Reportable quantity, section 304 of EPA's 1000 lb List of Lists)

butyl glycolether (111-76-2)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

15.2. International regulations

CANADA

No additional information available

EU-Regulations

No additional information available

National regulations

No additional information available

15.3. US State regulations

No additional information available

SECTION 16: Other information

Revision date : 04/15/2015 Other information : None.

Full text of H-phrases:

kt of 11 philases.	
Acute Tox. 2 (Inhalation:gas)	Acute toxicity (inhalation:gas) Category 2
Acute Tox. 3 (Dermal)	Acute toxicity (dermal) Category 3
Acute Tox. 3 (Oral)	Acute toxicity (oral) Category 3
Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Flam. Liq. 4	Flammable liquids Category 4
Skin Corr. 1A	Skin corrosion/irritation Category 1A
Skin Corr. 1B	Skin corrosion/irritation Category 1B
Skin Irrit. 2	Skin corrosion/irritation Category 2
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H227	Combustible liquid
H301	Toxic if swallowed
H302	Harmful if swallowed
H311	Toxic in contact with skin
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H319	Causes serious eye irritation
H330	Fatal if inhaled
H335	May cause respiratory irritation

07/16/2015 EN (English US) 7/8

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

HMIS III Rating

Health : 2 Moderate Hazard - Temporary or minor injury may occur

Flammability : 0 Minimal Hazard - Materials that will not burn

Physical : 0 Minimal Hazard - Materials that are normally stable, even under fire conditions, and will NOT

react with water, polymerize, decompose, condense, or self-react. Non-Explosives.

Personal Protection : E

B - Safety glasses, Gloves

SDS US (GHS HazCom 2012)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product

07/16/2015 EN (English US) 8/8